


SKR33 Without Cover, Motor Wrap

Model SKR33□□C (with a Single Short Block)

Model SKR33□□D (with Two Short Blocks)

For model number coding, see **A2-28**.



With bottom side motor wrap

Short block details

B'-B' cross section

¹ Distance between the mechanical stopper and the stroke starting position.

Stroke (mm) (stroke between mechanical stoppers)		Outer rail length (mm)	Overall length L_1 (mm)	C (mm)	G (mm)	P (mm)	F (mm)	H (mm)	n	n_1	Overall main unit mass (kg)	
Type C	Type D ¹										Type C	Type D
70 (80.5)	20 (30)	150	214	100	25	100	100	25	2	2	2	2.2
120 (130.5)	70 (80)	200	264	100	50	100	100	50	2	2	2.4	2.6
220 (230.5)	170 (180)	300	364	200	50	200	200	50	3	2	3.1	3.3
320 (330.5)	270 (280)	400	464	300	50	200	200	100	4	2	3.8	4
420 (430.5)	370 (380)	500	564	400	50	200	400	50	5	3	4.6	4.8
520 (530.5)	470 (480)	600	664	500	50	200	400	100	6	3	5.3	5.5
620 (630.5)	570 (580)	700	764	600	50	200	600	50	7	4	6	6.2


¹ Indicates a value when two inner blocks are in close contact with each other.

SKR33 With Cover, Motor Wrap

Model SKR33□□C (with a Single Short Block)

Model SKR33□□D (with Two Short Blocks)

For model number coding, see **A2-28**.



Stroke (mm) (stroke between mechanical stoppers)		Outer rail length (mm)	Overall length L_1 (mm)	C (mm)	G (mm)	P (mm)	F (mm)	H (mm)	n	n_1	Overall main unit mass (kg)	
Type C	Type D ¹										Type C	Type D
70 (80.5)	20 (30)	150	214	100	25	100	100	25	2	2	2.2	2.5
120 (130.5)	70 (80)	200	264	100	50	100	100	50	2	2	2.6	2.9
220 (230.5)	170 (180)	300	364	200	50	200	200	50	3	2	3.4	3.7
320 (330.5)	270 (280)	400	464	300	50	200	200	100	4	2	4.1	4.4
420 (430.5)	370 (380)	500	564	400	50	200	400	50	5	3	4.9	5.2
520 (530.5)	470 (480)	600	664	500	50	200	400	100	6	3	5.7	6
620 (630.5)	570 (580)	700	764	600	50	200	600	50	7	4	6.4	6.7

¹ Indicates a value when two inner blocks are in close contact with each other.